

Guidelines for the installation of Tobermore Historic Circle

Planning your patio

- Planning your patio before starting will make it quicker and easier to lay. Make a scale plan of your garden and draw various designs, taking into consideration, where will receive most sun and how you can minimise cutting. Mark out your final design using lengths of string to check that you are happy with the layout.

Note: At Tobermore we have in-house designers who will be able to advise you on your design.

Points to remember before starting

- Your patio must be at least 150mm below the damp-proof course (DPC) of your house so some excavation may be required. You will need somewhere to put this excavated material - so if you can't have it taken away perhaps you could construct a rockery elsewhere in the garden.
- If you want to incorporate outdoor lighting around your patio it is easier to run cables before starting.
- The finished level of your patio should be level with the adjoining lawn so that you create a mowing edge to avoid damaging your lawn mower blades.
- If your patio is being laid against the wall of your house, a fall must be incorporated to allow water to flow away. See details on drainage and falls.

Drainage and falls

- The flag surface requires a minimum crossfall of 1:70, to avoid water lying on the surface. If necessary, drainage gullies can be installed to catch the water where runoff is not possible.

Laying the flags

These are basic guidelines on how to install paving flags, please refer to the relevant British Standard for more information, details on reverse.

1. Sharp sand 20-40mm is screeded over the sub-base and compacted using a plate vibrator.
2. Begin laying the flags and ensure any uneven areas in the bedding layer are repaired using a hand trowel.
3. When laying the flags always ensure you allow a 2-3mm joint.
4. Use a level and hammer to ensure flags are laid evenly.

Jointing the flags

Joints should be filled with either:

1. Jointing Sand (Brush in jointing sand ensuring all joints are filled);
2. Rompox; or
3. Mortar (Extreme care must be taken as it will stain the surface).

Jointing the flags

Joints should be filled with either:

1. Jointing Sand (Brush in jointing sand ensuring all joints are filled);
2. Rompox; or
3. Mortar (Extreme care must be taken as it will stain the surface).


Please note

Jointing sand, grit and Rompox are purchased separately to the flags and are available from Tobermore.

Flags may be cut with a guillotine or power saw to suit curved edges, manholes etc.

1 Historic Circle pack contains:

The flag surface requires a minimum crossfall of 1:70, to avoid water lying on the surface. If necessary, drainage gullies can be installed to catch the water where runoff is not possible.



Add that finishing touch

Once you have finished your patio you should think of how best to add that unique finishing touch. A patio should be used like any other room in the house and therefore time should be taken to decorate it.

Plants, pots, outdoor ornaments, garden furniture and flower filled tubs can all add colour to your patio. Or go a stage further and build a pergola or add a water feature. A little bit of creative thinking will add character to your outdoor room, which will continue to improve as the years go by.

Instructions & Warnings

As referred to in Tobermore's Conditions of Sale

CORE TERMS (PAVING & WALLING)

Product

All products should be carefully inspected for defects or damage upon delivery and prior to being laid or fitted.

Product Information

Within Tobermore, design and development of products is a continuing process, and product information is subject to change without notice. Accordingly, please check with Tobermore to ensure that the product information you have represents the most up-to-date product information.

Installation

All products should be installed in accordance with the latest British Standard.

Colour

Tobermore produces paving and walling products with excellent density and durability, however, as with all concrete products, slight colour variations are inevitable. Although every effort is made to ensure consistency of product colour, variations can occur. In particular, single colours such as Golden, Buff, Natural, Charcoal and Red will have variations. Tobermore therefore recommends that products are thoroughly mixed on site by drawing from a minimum of four pallets.

We would always recommend that when purchasing products, especially in larger quantities, that they are all ordered and manufactured in one batch to reduce the chances of getting colour variation.

Please note that the colour of new products will inevitably vary compared to those which have been installed for a period of time as weathering does take place.

All colour illustrations in Tobermore's brochures are as accurate as the printing process will allow. For a more accurate colour match please refer to actual product samples, which can be provided.

Efflorescence

Efflorescence is a white crystalline deposit that occurs naturally on the surface of concrete materials. Tobermore use market leading technology to significantly suppress the occurrence of efflorescence, however, if it occurs, it may mask the colour of the product for a period of time, but tends to be washed away gradually by rain. Tobermore do not replace products with efflorescence. Packs of products which have had packaging removed should always be re-covered with appropriate packaging to prevent the occurrence of secondary efflorescence.

Surface Scratches

Minor scuffs or bruises may occur during delivery, movement on-site, and installation (for example, during any plate vibrating process). In Tobermore's experience, these marks usually weather off through time. (EasyClean products are protected with a glue dot)

Ordering

To avoid waste, please ensure that your contractor accurately measures the area on site before ordering products. In Tobermore's experience, dimensions taken from a project plan can vary significantly from the final layout.

Manufacturing & Quality Systems

Tobermore is a BS EN ISO 9001, BS EN ISO 14001 and BES 6001 registered company. Tobermore uses an integrated management system to manage all health & safety and environmental issues.

Product Maintenance

Routine cleaning and maintenance is required to keep the overall appearance of products in pristine condition.

Laying multi-blend coloured paving blocks, flags and walling products

To achieve an even blend of colour when laying multi-blend paving blocks, flags and walling products, it is desirable to mix from three or four different pallets.

Queries & Complaints

Please contact one of Tobermore's Paving & Walling Centres or offices (contact details at www.tobermore.co.uk) with any queries or complaints. Any complaints must be notified to Tobermore without delay.

CORE TERMS (PAVING ONLY)

Product Maintenance

Light coloured paving blocks and flags emphasise tyre marks and oil spills on the driveway. Please note that these products will need more maintenance if overall appearance is to be maintained.

Initial Cleaning

When an area has just been paved, allow it to settle for a few days. After this, you may wish to lightly hose down the paving to remove any excess sand or dirt. The area should then be treated with a weed killer suppressant two – three times per year as required.

General Cleaning

Paving requires regular maintenance, including regular sweeping to prevent the build up of detritus. Tobermore recommends that paving is cleaned two – three times per year.

For general cleaning of dirt and algae, vigorous brushing with a stiff yard brush with plenty of hot detergent solution (washing up liquid or non-bio washing powder), thoroughly rinsed with clean water, should suffice. Repeated treatment may be required for paved areas sited beneath trees or in permanent/near permanent shade.

A light power hose at medium pressure is generally all that is required to clean general dirt and grime. Any jointing material which is removed must be replaced. Do not use high pressure powerwashers as aggressive power-washing can damage the product surface. A trial area should be tested before large scale powerwashing takes place. (Important: EasyClean products should not be pressure washed. Please refer to specific EasyClean information)

Moss, Lichen and Algae

Thick growths of moss or lichen must be removed first by scraping out the joints and then treating the area with a moss killer such as anti-moss paving cleaner. Anti-moss is designed to remove moss, lichens and algae. It is best applied in dry weather. After being applied it will take a few days to be fully effective. Once the moss and lichens have been killed, they can easily be brushed off. Anti-moss also leaves a residue in the sand joint which will help reduce the likelihood of re-growth. The manufacturer's instructions should always be followed when using any cleaning agent.

Weeds

Large weeds should be removed by hand and then the area treated with a weed killer (available from any good garden centre). Smaller weeds can then be treated directly with weed killer and these weeds should start to die within days. The manufacturer's instructions should always be followed when using any weed killing agent.

Block Paving Sealer

It is possible to seal block paving with a resin material which combats staining and weed growth and which also enhances colour and appearance. The acrylic sealer is sprayed onto the block paving and forms a 'skin' on top of the paving and the jointing material giving an easily maintained finish. The manufacturer's instructions should always be followed when using any sealing agent. (Important: Do not use sealers on EasyClean products)